

**ASTM E 90 SOUND TRANSMISSION LOSS
TEST REPORT**

Rendered to:

MI WINDOWS AND DOORS, INC.

SERIES/MODEL: 1650PW

TYPE: Fixed Window

Summary of Test Results			
ATI Data File No.	Glazing Option (Nominal Dimensions)	STC	OITC
82671.01A	7/8" IG (1/8" annealed, 1/4" air space, 1/8" annealed, 1/4" air space, 1/8" annealed)	30	26
82671.01B	7/8" IG (1/8" annealed, 5/8" air space, 1/8" annealed)	28	22

Reference should be made to ATI Report No. 82671.01-113-11 for complete test specimen description. The complete test results are listed in Appendix B.

ACOUSTICAL PERFORMANCE TEST REPORT

Rendered to:

MI WINDOWS AND DOORS, INC.
P.O. Box 370
650 West Market Street
Gratz, Pennsylvania 17030-0370

Report No: 82671.01-113-11
Test Date: 04/25/08
Report Date: 05/13/08
Expiration Date: 04/25/12

Test Sample Identification:

Series/Model: 1650PW

Type: Fixed Window

Overall Size: 47-1/4" by 59"

Glazing Option A (Nominal Dimensions): 7/8" IG (1/8" Annealed, 1/4" Air Space,
1/8" Annealed, 1/4" Air Space, 1/8" Annealed)

Glazing Option B (Nominal Dimensions): 7/8" IG (1/8" Annealed, 5/8" Air Space,
1/8" Annealed)

Project Scope: Architectural Testing, Inc. was contracted by MI Windows and Doors, Inc. to conduct sound transmission loss tests on Series/Model 1650PW, fixed windows. A summary of the results is listed in the Test Results section and the complete test data is included as Appendix B of this report. The sample was provided by the client.

Test Methods: The acoustical tests were conducted in accordance with the following:

ASTM E 90-04, *Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions.*

ASTM E 413-04, *Classification for Rating Sound Insulation.*

ASTM E 1332-90 (Re-approved 2003), *Standard Classification for Determination of Outdoor-Indoor Transmission Class.*

ASTM E 2235-04, *Standard Test Method for Determination of Decay Rates for Use in Sound Insulation Test Methods.*

Test Equipment: The equipment used to conduct these tests meets the requirements of ASTM E 90. The microphones were calibrated before conducting sound transmission loss tests. The test equipment and test chamber descriptions are listed in Appendix A.

Sample Installation:

Sound transmission loss tests were initially performed on a filler wall that was designed to test 48" by 72" and 72" by 48" specimens. The filler wall achieved an STC rating of 63.

A filler wall reducing element was used to reduce the test opening size to 47-3/4" wide by 59-1/2" high. The reducing element consisted of a double 2x4 wood stud wall construction with three layers of 5/8" drywall on both sides. The stud cavities in the wall were insulated with two layers of R-13 fiberglass insulation. The window was placed on a foam isolation pad in the new test opening. Duct seal was used to seal the perimeter of the window to the test opening on both sides. The interior side of the window frame, when installed, was approximately 1/4" from being flush with the receiving room side of the filler wall. A stethoscope was used to check for any abnormal air leaks around the test specimen prior to testing.

Test Procedure: The sound transmission loss test consisted of the following measurements: One background noise sound pressure level and five sound absorption measurements were conducted at each of the five microphone positions. Two sound pressure level measurements were made simultaneously in both rooms, at each of the five microphone positions. The air temperature and relative humidity conditions were monitored and recorded during the background, absorption, source, and receive room measurements.

Sample Descriptions:

Frame Construction:

		Frame
Size		47-1/4" by 59"
Thickness		4"
Corners		Mitered
	Fasteners	Welds
	Seal Method	None
Material		Vinyl
	Reinforcement	N/A
	Thermal Break Material	N/A
Daylight Opening Size		41-1/2" by 53-1/4"

Glazing Option A:

Measured Overall Insulation Glass Unit Thickness		0.822"
Spacer Type	Aluminum	

	Exterior Sheet	Gap	Middle Sheet	Gap	Interior Sheet
Measured Thickness	0.116"	0.235"	0.115"	0.240"	0.116"
Muntin Pattern	N/A	N/A	N/A	N/A	N/A
Material	Annealed	Air*	Annealed	Air*	Annealed
Laminate Material	N/A	N/A	N/A	N/A	N/A

Glazing Method	Interior
Glazing Material	Silicone
Glazing Bead Material	Vinyl

* - Stated per Client/Manufacturer, N/A-Non Applicable

Sample Descriptions: (Continued)

Glazing Option B:

Measured Overall Insulation Glass Unit Thickness	0.882"
Spacer Type	Steel U Shaped

	Exterior Sheet	Gap	Interior Sheet
Measured Thickness	0.116"	0.650"	0.116"
Muntin Pattern	N/A	N/A	N/A
Material	Annealed	Air*	Annealed
Laminate Material	N/A	N/A	N/A

Glazing Method	Interior
Glazing Material	Silicone
Glazing Bead Material	Vinyl

* - Stated per Client/Manufacturer, N/A-Non Applicable

Sample Descriptions: (Continued)

Components:

TYPE	QUANTITY	LOCATION
Weatherstrip		
No weatherstrip	N/A	N/A
Hardware		
No hardware	N/A	N/A
Drainage		
1/4" Weep louver	4	2 on sill track at glazing, 2 in sill hollow
1" by 1/8" Weepslot	2	Sill face

Comments: The weight of the sample for glazing option A was 88 lbs. The weight of the sample for glazing option B was 64 lbs. The design drawings (included in Appendix C) supplied by the client, accurately describe the Series/Model 1650PW, fixed window. The dimensions on the drawings that are circled and/or checked were verified against the test specimen. The fixed window was disassembled, and the components will be retained by ATI for four years. Photographs of the test specimen are included in Appendix D.

Test Results: The STC (Sound Transmission Class) rating was calculated in accordance with ASTM E 413. The OITC (Outdoor-Indoor Transmission Class) was calculated in accordance with ASTM E 1332. A summary of the sound transmission loss test results on the Series/Model 1650PW, fixed window is listed below.

Summary of Test Results			
ATI Data File No.	Glazing Option (Nominal Dimensions)	STC	OITC
82671.01A	7/8" IG (1/8" annealed, 1/4" air space, 1/8" annealed, 1/4" air space, 1/8" annealed)	30	26
82671.01B	7/8" IG (1/8" annealed, 5/8" air space, 1/8" annealed)	28	22

The complete test results are listed in Appendix B. Flanking limit tests and reference specimen tests are available upon request.

Detailed drawings, data sheets, representative samples of test specimens, a copy of this report, or other pertinent project documentation will be retained by Architectural Testing, Inc. for a period of four years from the original test date. At the end of this retention period, such materials shall be discarded without notice and the service life of this report will expire. Results obtained are tested values and were secured by using the designated test methods. This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. It is the exclusive property of the client so named herein and relates only to the specimen(s) tested. This report may not be reproduced, except in full, without the written approval of Architectural Testing, Inc.

For ARCHITECTURAL TESTING, INC:


Brandon C. Ward
Technician - Acoustical Testing

Todd D. Kister
Laboratory Supervisor - Acoustical Testing

BCW:crc

Attachments (pages): This report is complete only when all attachments listed are included.

- Appendix-A: Equipment description (1)
- Appendix-B: Complete test results (4)
- Appendix-C: Drawings (4)
- Appendix-D: Photographs (1)

	Architectural Testing, Inc is accredited by the International Accreditation Service, Inc. (IAS) under the specific test methods listed under lab code TL-144, in accordance with the recognized International Standard ISO/IEC 17025:2005. The laboratory's accreditation or test report in no way constitutes or implies product certification, approval, or endorsement by IAS. This test report applies only to the specimen that was tested.
---	--

Revision Log

<u>Rev. #</u>	<u>Date</u>	<u>Page(s)</u>	<u>Revision(s)</u>
0	05/13/08	N/A	Original Report Issue

Appendix A

Instrumentation:

Instrument	Manufacturer	Model	Description	ATI Number
Analyzer	Agilent Technologies	35670A	Dynamic signal analyzer	Y002929
Receive Room Microphone	G.R.A.S.	40AR	1/2", pressure type, condenser microphone	Y003246
Source Room Microphone	G.R.A.S.	40AR	1/2", pressure type, condenser microphone	Y003245
Receive Room Preamp	G.R.A.S.	26AK	1/2" preamplifier	Y003249
Source Room Preamp	G.R.A.S.	26AK	1/2" preamplifier	Y003248
Microphone Calibrator	Bruel & Kjaer	4228	Pistonphone calibrator	Y002816
Noise Source	Delta Electronics	SNG-1	Two, non-coherelated "Pink" noise signals	Y002181
Equalizer	Rane	RPE228	Programmable EQ	Y002180
Power Amplifiers	Renkus-Heinz	P2000	2 - Amplifiers	Y002179 Y001779
Receive Room Loudspeakers	Renkus-Heinz	Trap Jr/9"	2 - Loudspeakers	Y001784 Y001785
Source Room Loudspeakers	Renkus-Heinz	Trap Jr/9"	2 - Loudspeakers	Y002649 Y002650

Test Chamber:

	Volume	Description
Receiving Room	8291.3 ft ³ (234 m ³)	Rotating vane and stationary diffusers. Temperature and humidity controlled. Isolation pads under the floor.
Source Room	7296.3 ft ³ (206.6 m ³)	Stationary diffusers only. Temperature and humidity controlled.

	Maximum Size	Description
TL Test Opening	14 ft wide by 10 ft high	Vibration break between source and receive rooms.

Appendix B
Complete Test Results



SOUND TRANSMISSION LOSS

ASTM E90

Architectural Testing


ATI No.	82671.01A	Date	04/25/08
Client	MI Windows and Doors, Inc.		
Specimen	Series/Model 1650PW, fixed window with 7/8" IG (1/8" annealed, 1/4" air space, 1/8" annealed, 1/4" air space, 1/8" annealed)		
Specimen Area	19.36 Sq Ft		
Filler Area	120.64 Sq Ft		
Operator	Brandon C. Ward		

	Bkgrd	Absorp	Source	Receive	Filler	Specimen
Temp F	74.8	75.1	74.7	75.2	72.8	74.9
RH %	44.5	44.9	43.8	45.3	43.0	44.7

Freq (Hz)	Bkgrd SPL (dB)	Absorp (Sabines /Sq Ft)	Source SPL (dB)	Receive SPL (dB)	Filler TL (dB)	Specimen TL (dB)	95% Conf Limit	No. of Deficiencies	Trans Coef Diff
80	44.4	56.0	85.8	61.7	36.1	20	3.47	0	8.6
100	38.9	62.1	87.9	61.4	39.1	22	4.08	0	9.6
125	39.0	51.1	93.5	62.8	48.6	27	3.24	0	14.2
160	40.1	49.1	94.6	65.6	47.2	25	0.76	0	14.2
200	40.0	51.3	99.7	72.4	49.1	23	0.83	0	18.0
250	36.2	50.7	100.9	75.6	52.5	21	1.83	2	23.4
315	34.3	58.8	99.6	75.7	54.2	19	0.97	7	27.2
400	32.3	60.1	98.8	72.6	58.1	21	1.01	8	28.8
500	31.4	58.7	99.9	69.5	61.0	26	0.43	4	27.4
630	26.1	57.4	102.5	68.3	63.8	29	0.74	2	26.4
800	27.0	60.3	102.5	64.7	66.3	33	0.21	0	25.5
1000	24.4	63.0	102.2	61.3	72.3	36	0.62	0	28.6
1250	24.3	68.9	105.7	60.2	80.0	40	0.54	0	32.1
1600	20.1	71.0	111.6	64.3	81.5	42	0.24	0	31.9
2000	14.2	75.7	107.5	59.8	82.1	42	0.34	0	32.4
2500	6.8	87.9	106.0	56.0	77.1	43	0.52	0	25.7
3150	6.7	102.9	107.0	57.7	79.2	42	0.30	0	29.3
4000	6.5	125.4	105.7	63.7	80.0	34	0.30	0	38.1
5000	6.9	167.0	104.0	60.8	79.5	34	0.50	0	37.7

STC Rating = 30 *(Sound Transmission Class)*
Deficiencies = 23 *(Number of deficiencies versus contour curve)*
OITC Rating = 26 *(Outdoor/Indoor Transmission Class)*


Note: *The acoustical chambers are qualified for measurements down to 80 hertz.
 Data reported below 80 hertz is for reference only.*

	Architectural Testing, Inc is accredited by the International Accreditation Service, Inc. (IAS) under the specific test methods listed under lab code TL-144, in accordance with the recognized International Standard ISO/IEC 17025:2005. The laboratory's accreditation or test report in no way constitutes or implies product certification, approval, or endorsement by IAS. This test report applies only to the specimen that was tested.
---	--



Architectural Testing

ATI No. 82671.01A Date 04/25/08
Client MI Windows and Doors, Inc.
Specimen Series/Model 1650PW, fixed window with 7/8" IG (1/8" annealed, 1/4" air space, 1/8" annealed, 1/4" air space, 1/8" annealed)
Specimen Area 19.36 Sq Ft
Filler Area 120.64 Sq Ft
Operator Brandon C. Ward



Architectural Testing, Inc is accredited by the International Accreditation Service, Inc. (IAS) under the specific test methods listed under lab code TL-144, in accordance with the recognized International Standard ISO/IEC 17025:2005. The laboratory's accreditation or test report in no way constitutes or implies product certification, approval, or endorsement by IAS. This test report applies only to the specimen that was tested.



SOUND TRANSMISSION LOSS

ASTM E90

Architectural Testing


ATI No.	82671.01B	Date	04/25/08
Client	MI Windows and Doors, Inc.		
Specimen	Series/Model: 1650PW, fixed window with 7/8" IG (1/8" annealed, 5/8" air space, 1/8" annealed)		
Specimen Area	19.36 Sq Ft		
Filler Area	120.64 Sq Ft		
Operator	Brandon C. Ward		

	Bkgrd	Absorp	Source	Receive	Filler	Specimen
Temp F	75.6	75.4	74.5	75.4	72.8	75.2
RH %	41.3	41.3	36.1	41.4	43.0	40.0

Freq (Hz)	Bkgrd SPL (dB)	Absorp (Sabines /Sq Ft)	Source SPL (dB)	Receive SPL (dB)	Filler TL (dB)	Specimen TL (dB)	95% Conf Limit	No. of Deficiencies	Trans Coef Diff
80	43.7	56.6	86.0	62.7	36.1	19	3.20	0	9.6
100	39.6	59.9	88.0	63.8	39.1	20	3.00	0	11.9
125	38.1	48.9	93.7	65.7	48.6	24	2.95	0	16.7
160	43.8	50.5	94.8	69.5	47.2	21	0.70	0	18.2
200	41.9	52.0	99.9	79.0	49.1	17	0.77	1	24.5
250	36.8	53.9	100.9	82.5	52.5	14	1.74	7	30.5
315	36.1	58.0	99.9	77.9	54.2	17	0.98	7	29.0
400	35.4	61.4	99.1	75.5	58.1	19	1.08	8	31.6
500	34.3	58.0	100.2	72.5	61.0	23	0.64	5	30.2
630	28.5	57.9	102.8	70.7	63.8	27	0.82	2	28.6
800	29.5	59.3	102.8	66.3	66.3	32	0.26	0	26.8
1000	26.9	61.4	102.5	62.9	72.3	35	0.66	0	29.8
1250	27.1	70.8	105.8	61.1	80.0	39	0.56	0	32.9
1600	22.7	70.8	111.7	64.3	81.5	42	0.29	0	31.9
2000	15.9	77.2	107.6	59.9	82.1	42	0.32	0	32.4
2500	7.7	87.9	106.1	57.9	77.1	42	0.49	0	27.6
3150	7.9	104.9	107.0	59.5	79.2	40	0.30	0	31.1
4000	7.0	129.5	105.7	65.5	80.0	32	0.30	0	40.2
5000	7.0	171.0	103.8	61.5	79.5	33	0.44	0	38.7

STC Rating = 28 *(Sound Transmission Class)*
Deficiencies = 30 *(Number of deficiencies versus contour curve)*
OITC Rating = 22 *(Outdoor/Indoor Transmission Class)*


Note: *The acoustical chambers are qualified for measurements down to 80 hertz.
 Data reported below 80 hertz is for reference only.*

	Architectural Testing, Inc is accredited by the International Accreditation Service, Inc. (IAS) under the specific test methods listed under lab code TL-144, in accordance with the recognized International Standard ISO/IEC 17025:2005. The laboratory's accreditation or test report in no way constitutes or implies product certification, approval, or endorsement by IAS. This test report applies only to the specimen that was tested.
---	--




Architectural Testing

ATI No. 82671.01B Date 04/25/08
Client MI Windows and Doors, Inc.
Specimen Series/Model: 1650PW, fixed window with 7/8" IG (1/8" annealed, 5/8" air space, 1/8" annealed)
Specimen Area 19.36 Sq Ft
Filler Area 120.64 Sq Ft
Operator Brandon C. Ward



Architectural Testing, Inc is accredited by the International Accreditation Service, Inc. (IAS) under the specific test methods listed under lab code TL-144, in accordance with the recognized International Standard ISO/IEC 17025:2005. The laboratory's accreditation or test report in no way constitutes or implies product certification, approval, or endorsement by IAS. This test report applies only to the specimen that was tested.

Appendix C
Design Drawings



Architectural Testing

Test sample complies with these details.
Deviations are noted.

Report# 026A-01-13-11
Date 5-13-08
Tec. BCL



ACTUAL SIZE

NOTE:

MATERIAL - RIGID PVC
UNSPECIFIED WALL THICK. - .070
AREA - .087
WT/FT .054



MI WINDOWS AND DOORS


650 WEST MARKET STREET • GRATZ, PA • 17030-0370

TITLE 8500/8540/3500/3540/TX3250/9555
PLAIN GLAZING BEAD


LTR.	DESCRIPTION	BY	DATE
A	ADDED LEG - MORE CONTACT WITH GLASS	VR	1-29-03
	REVISIONS		

DFTM.	DATE	SCALE	DRAWING NO.	REV.
V.M.R.	7-24-02	5:1	V-637	A

BILL OF MATERIALS



No.	PART DESCRIPTION	PART No.	REQ'D	VENDOR	COST
1	MAIN FRAME (FINLESS)	8994/9091	4	MIKRON	
2	GLAZING BEAD	V-637	4	MIKRON	
3	GLASS SETTING BLOCK	3/16 x 7/8 x 7/8	2		
4	GLASS	7/8"	1	VARIOUS	
5	GLASS SPACER	11/16	4	INTERCEPT	
6	GLAZING TAPE	1/4 x 1/8	4	NORTON	
7	INSTALLATION SCREW PACK	TBD			
8	INSTALLATION SCREW PLUG	TBD			



Test sample complies with these details.
Deviations are noted.

Report # 82671.01-113-11
Date 5-13-08
Tech: BCW



XACT WINDOWS AND DOORS
650 West Market Street
Gratz, PA 17030

TITLE 1650/1680 DIRECT GLAZED PICTURE WDW
BILL OF MATERIALS


LTR.	DESCRIPTION	BY	DATE
	REVISIONS		
A	GLZ BEAD PART # CHGD FROM 8083 TO 8292	CAM	01-06-04
A	MF PART # CHGD FROM 8389 TO 8994	CAM	01-06-04

DFTM.	DATE	SCALE	DRAWING NO.	REV.
V.M.R.	5-5-01	~~~~~	BOM-1650PW	

option B only triple glazed with aluminum spacer

1/8 x 1/4 DOUBLE SIDED TAPE

INTERCEPT SPACER



7/8 INSUL GLASS

V-637 PLAIN BEAD

8994/9091 MAIN FRAME



Architectural Testing

Test sample complies with these details. Deviations are noted.

Report#

Date

8671.01-113-11 BCW

Tech

5-13-08



XACT WINDOWS AND DOORS
650 West Market Street
Gratz, PA 17030

TITLE

1650/1680 FINLESS PICTURE WINDOW





SCALE FULL

DATE 2-18-00

DESCRIPTION 1650PW-AS1 DIRECT GLAZED

REV. A

REV.	DATE	DESCRIPTION
A	8-9-04	UPDATED EXTRUSIONS/PART NOS.



Test sample complies with these details.
Deviations are noted

Report# 80671.01-113-11
Date 5/13-08 Tech BCW

Appendix D
Photographs



Sample Installed in Test Chamber