



Pro5000 Series

Window Series	Grids	Glazing Type	STC	U-Value	SHGC	VLT	Energy Star Compliance	High Performance Low-E Option			HP Energy Star Compliance
								U-Value	SHGC	VLT	
5500 Single Hung	No Grids	Clear Insulated	26	0.47	0.65	0.68					
		Low-E Insulated	26	0.33	0.30	0.57		0.33	0.23	0.45	S
		Low-E Insulated w/ argon	26	0.29	0.30	0.57	NC	0.29	0.23	0.45	NC, SC, S
	Grids	Clear Insulated	26	0.47	0.59	0.61					
		Low-E Insulated	26	0.33	0.27	0.51		0.33	0.21	0.40	S
		Low-E Insulated w/ argon	26	0.29	0.27	0.51	NC	0.29	0.21	0.40	NC, SC, S
5610 Picture Window	No Grids	Clear Insulated	29	0.47	0.69	0.73					
		Low-E Insulated	29	0.31	0.33	0.62		0.31	0.25	0.48	S
		Low-E Insulated w/ argon	29	0.27	0.33	0.62	N, NC	0.27	0.25	0.48	N, NC, SC, S
	Grids	Clear Insulated	29	0.47	0.63	0.66					
		Low-E Insulated	29	0.31	0.30	0.55		0.31	0.23	0.44	S
		Low-E Insulated w/ argon	29	0.27	0.30	0.55	N, NC	0.27	0.23	0.44	N, NC, SC, S
5800 Single Slider	No Grids	Clear Insulated		0.48	0.66	0.69					
		Low-E Insulated		0.33	0.31	0.58		0.33	0.24	0.45	S
		Low-E Insulated w/ argon		0.29	0.31	0.58	NC	0.29	0.23	0.45	NC, SC, S
	Grids	Clear Insulated		0.48	0.59	0.62					
		Low-E Insulated		0.33	0.28	0.52		0.33	0.21	0.41	S
		Low-E Insulated w/ argon		0.29	0.28	0.52	NC	0.29	0.21	0.41	NC, SC, S