



# 1500 Series

Window Series	Grids	Glazing Type	STC	U-Value	SHGC	VLT	Energy Star Compliance	High Performance Low-E Option			HP Energy Star Compliance
								U-Value	SHGC	VLT	
1555 Double Hung	No Grids	Clear Insulated		0.43	0.57	0.60					
		Low-E Insulated		0.32	0.29	0.51		0.32	0.21	0.41	S
		Low-E Insulated w/ argon		0.29	0.29	0.51	NC	0.29	0.21	0.41	NC, SC, S
	Grids	Clear Insulated		0.43	0.51	0.54					
		Low-E Insulated		0.32	0.26	0.46		0.32	0.19	0.36	S
		Low-E Insulated w/ argon		0.29	0.26	0.46	NC	0.29	0.19	0.36	NC, SC, S
1556 Double Hung	No Grids	Clear Insulated		0.43	0.57	0.60					
		Low-E Insulated		0.32	0.29	0.51		0.32	0.21	0.41	S
		Low-E Insulated w/ argon		0.29	0.29	0.51	NC	0.29	0.21	0.41	NC, SC, S
	Grids	Clear Insulated		0.43	0.51	0.54					
		Low-E Insulated		0.32	0.26	0.46		0.32	0.19	0.36	S
		Low-E Insulated w/ argon		0.29	0.26	0.46	NC	0.29	0.19	0.36	NC, SC, S
1555 Picture Window	No Grids	Clear Insulated		0.45	0.62	0.65					
		Low-E Insulated		0.31	0.31	0.55		0.31	0.23	0.44	S
		Low-E Insulated w/ argon		0.28	0.31	0.55		0.27	0.22	0.44	N, NC, SC, S
	Grids	Clear Insulated		0.45	0.55	0.58					
		Low-E Insulated		0.31	0.28	0.49		0.31	0.21	0.39	S
		Low-E Insulated w/ argon		0.28	0.28	0.49	NC	0.27	0.20	0.39	N, NC, SC, S

**Assumptions:**

Spacer = Duraseal; LowE = RLE7036; HP LowE = RLE5527 (x1); Glass thickness = DSB/DSB

Updated 10/8/18