



Mi Professional 5000

Egress by Min Width or Min Height

Operation	Minimum Width		Minimum Height	
	Width	Height	Width	Height
Single Hung	28.5"	71.5"	37.5"	55"
2-Lite Slider	47.5"	42.5"	75.5"	27.125"
3-Lite Slider	95.5"	42.5"	120"	34.5"

Standard Egress Sizes

***with a 60 bottom sash

Nominal Size	Exact Dimensions	Single Hung	Slider	XOX
3050	35-1/2 x 59-1/2	X		
3056	35-1/2 x 65-1/2	X		
3060	35-1/2 x 71-1/2	X		
3070	35-1/2 x 83-1/2	X***		
3080	35-1/2 x 95-1/2	X***		
3650	41-1/2 x 59-1/2	X		
3656	41-1/2 x 65-1/2	X		
3660	41-1/2 x 71-1/2	X		
4040	47-1/2 x 47-1/2		X	
4050	47-1/2 x 59-1/2		X	
4056	47-1/2 x 65-1/2		X	
4060	47-1/2 x 71-1/2		X	
4640	53-1/2 x 47-1/2		X	
5036	59-1/2 x 41-1/2		X	
5040	59-1/2 x 47-1/2		X	
5046	59-1/2 x 53-1/2		X	
6030	71-1/2 x 35-1/2		X	
8040	95-1/2 x 47-1/2			X
8050	95-1/2 x 59-1/2			X
8060	95-1/2 x 71-1/2			X
10030	119-1/2 x 35-1/2			X

An egress window must satisfy the following International Residential Code (IRC) criteria:

1. Minimum width opening - 20"
2. Minimum height opening - 24"
3. Minimum net clear opening, ground floor - 5.0 sq ft
4. Minimum net clear opening, all other floors - 5.7 sq ft
5. Maximum latch height above floor - 54 inches
6. Maximum sill height above floor - 44 inches

Please check and follow your local building code requirements, as they may differ.