



V2000 Series Single-hung window

MODELS 1355 & 4300

Popular with builders, contractors, and homeowners, these single-hung windows merge aesthetic qualities with energy-efficient attributes. Combining a traditional brickmould exterior and timeless color options with optimally placed metal reinforcements and a constant-force balance system, these single-hung windows provide beauty and long-lasting strength and performance for new and existing homes.



What you can expect

ENERGY-EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

CONVENIENCE AND STYLE

- Brickmould exterior profile creates timeless appeal
- Surface-mounted, forced-entry-resistant locks provide a stronger, safer seal
- Full-length lift rail and constant-force balance system for easy opening and closing
- Tilt-in bottom sash for easy cleaning
- True-sloping sill optimizes water drainage and eliminates need for weep holes
- Easy sash and fixed glass removal for efficient drywall pass through during construction
- Optional window operating control device for enhanced safety



Engineered to perform

- Welded, multi-chamber frame and sash
- Metal-reinforced lock rail and bottom sash
- Available frame styles: mounting fin, finless
- 3 ¼" frame depth
- Integral J-channel
- Available with 3 ½" flat casing and factory-applied drywall returns
- Wood extension jambs available for 4 ⅞" and 6 ⅞" wall depths

Min and max sizing

WIDTH		HEIGHT	
MIN	MAX	MIN	MAX
16 ¼"	48"	23"	78"
CONTINUOUS HEAD & SILL (CHS)* MAX			
Twin (Each Window)	37 ¾"	74"	
Twin (Overall Unit)	75 ⅝"	74"	
Triple (Each Window)	35 ¾"	74"	
Triple (Overall Unit)	108"	74"	

Available in 1/8" increments. DP upgrade required for any unit greater than 84" tall.
CHS available on XX, OO, XXX, and OOO configurations.

Energy efficient glass

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Low-E glass	0.33	0.28	29
Low-E glass with grids	0.33	0.25	29
Argon and Low-E glass	0.29	0.28	29
Argon and Low-E glass with grids	0.29	0.25	29
HP Low-E glass	0.33	0.23	29
HP Low-E glass with grids	0.33	0.20	29
Argon and HP Low-E glass	0.30	0.22	29
Argon and HP Low-E glass with grids	0.30	0.20	29
Triple-pane SSB and Argon glass	0.23	0.23	29
Triple-pane SSB and Argon glass with grids	0.24	0.21	29

Note: all values based on standard 3/4" dual-pane insulated glass unit unless noted otherwise



V2000 SERIES
SINGLE HUNG WINDOW

See additional product and warranty information online.



Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/windows/V2000/single-hung

Create a customized look

Enhance your home's spaces with a variety of finish options and grid configurations.

FINISH OPTIONS

EXTERIOR

White EXTRUSION
Almond EXTRUSION / PAINT ◊
Clay EXTRUSION †
Bronze PAINT ◊
Black Matte PAINT ◊

INTERIOR

White EXTRUSION
Almond EXTRUSION
Clay EXTRUSION †

COMMON GRID TYPES



Flat
Grids-Between-
the-Glass



Sculptured
Grids-Between-
the-Glass



Simulated
Divided Lite

◊ Exterior paint not available with clay interior