

The 100 Series sliding glass doors allow homeowners to effortlessly blend interior and exterior spaces for new construction and replacement projects. Featuring an advanced roller system, the panels slide smoothly during operation and with an optional extended sill leg, the door meets DP55 requirements. 100 Series doors are available in multi-slide configurations up to 24′ wide by 10′ tall and are also available with the StormArmor™ impact-resistant product enhancement for storm-prone coastal applications.

PERFORMANCE FEATURES

- Warm-edge spacer system maximizes energy efficiency and improves seal performance of insulated glass units
- Woolpile weatherstripping aid in enhanced performance ratings
- Tandem composite adjustable rollers for ease of operation



Designed smarter, from the inside out

SIZING & OPERATION

PANELS/	PANEL OPERATION	STANDARD SIZES WIDTH		CUSTOM SIZES WIDTH HEIGHT			НT
TYPE	View from Outside In	Code	Exact	Min	Max	Min	Max
2-Panel (120)	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	(50)	60"	59"	96"	75"	120"
		(60)	72"				
		(80)	96"				
3-Panel (120)	○ X ○ ○ X ○ ·-→	(90)	108 7/8"	- 59"	144 7/8"	75"	120"
		(120)	144 ⁷ /8"				
4-Panel (120)	○ X X ○ ··· ←··	(120)	142 ⁵ / ₈ "	120"	190 5/8"	75"	120"
		(160)	190 5/8"				
3-Panel (130)	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	(90)	105 3/4"	- 88"	141 3/4"	75"	120"
		(120)	141 3/4"				
5-Panel (130)	○ X X I ○ ○ I X X ○	(126)	146 3/8"	146 ³/8"	236 3/8"	75"	120"
		(150)	176 ³/s"				
		(200)	236 3/8"				
6-Panel (130)	O X X O	(180)	210 1/8"	210 1/8"	282 1/8"	75"	120"
		(240)	282 1/8"				
4-Panel (140)	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	(120)	139 1/2"	117"	187 1/2"	75"	120"
		(160)	187 1/2"				
120=2-track; 130=3-track; 140=4-track	X=operating; O=stationary; I=intermediate Pocket configurations available	Available heights (68) 80", (80) 96", (90) 108" or (100) 120"		= Available with StormArmor			

ENERGY-EFFICIENT GLASS PACKAGES

Our dual-pane insulated glass package options help save on heating and cooling costs while enhancing home comfort

- In cool weather, insulated glass provides outstanding thermal performance to keep interior glass surfaces closer to room temperature, eliminating cold spots near doors
- In warm weather, it helps reduce solar heat gain and minimize glare to improve interior comfort

GLAZING TYPE	U-VALUE	SHGC	
HP Low-E glass	0.69	0.21	
HP Low-E glass with grids	0.69	0.19	
Argon and Lodz-340 glass	0.66	0.14	
Argon and Lodz-340 glass with grids	0.66	0.13	
Impact-resistant laminated glass with Argon and Lodz-366	0.65	0.21	
Impact-resistant laminated glass with Argon , Lodz-366 with grids	0.66	0.19	
Impact-resistant laminated glass with Argon and Lodz-340	0.65	0.15	
Impact-resistant laminated glass with Argon , Lo \bar{E}^3 -340 with grids	0.67	0.13	

Note: all values based on 120 door with dual-pane IGU







ENGINEERED TO PERFORM

- Sill depth
 - 120 door-6 ⁷/₃₂"
 - 130 door-8 7/16"
 - 140 door-10 ³/₃₂"
- 1½16" insulated glass unit
- DP55-DP80 rating (dependent on size and sill leg)
- Optional 2 ⁵/₈" or 3 ½ sill leg adapters
- StormArmor package includes impactresistant glass with HP low-E, argon, and preserve film to protect the glass until installation is complete

CONVENIENCE & STYLE

100 series doors are available with the following design details:

- Two-, three-, and four- panel configurations
- Pocket door available
- Keylock available
- Extruded aluminum screen available (not available on 4-track or pocket configurations)

SAFETY & SECURITY FEATURES

- Exterior wet glazing ensures optimal coastal performance
- Standard ³/₁₆" tempered glass is four times stronger than non-tempered glass and safer if broken

CREATE A CUSTOMIZED LOOK

GRID TYPES & SIZES

■ %" flat grids-between-the-glass

COMMON GRID PATTERNS







Perimeter



Drop

FRAME COLORS







White

Clay

Bronze



OUR MISSION

Getting It Right Every Time

We build each of our products the same way we built our company: with integrity and precision. Every MI window and door is handcrafted in the United States using state-of-the-art manufacturing techniques, and is backed by vigorous in-house testing procedures. We are 100% committed to offering the styles, value, and performance you're after.

Discover everything we have to offer at miwindows.com, or by calling 1-717-365-3300.