



## V2000 Series Single-hung window

### MODEL 3540

Boasting a stylish look, the 3540 single-hung window is specifically designed to meet high design pressure (DP) requirements for new home construction and remodeling and replacement projects. The removable meeting rail, sash, and top-glass allow for easy drywall pass-through while multiple color options, stylish beveled profile, full-length lift rail, and metal reinforcements at the meeting rail provide homeowners with aesthetic options and desirable performance.



## What you can expect

### ENERGY-EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

### CONVENIENCE AND STYLE

- Beveled exterior profile creates a clean, timeless aesthetic
- Surface-mounted tilt latches and forced-entry-resistant locks provide a stronger, safer seal
- Full-length lift rail for easy opening and closing
- Tilt-in bottom sash for easy cleaning
- Optional window operating control device for enhanced safety



## Engineered to perform

- Welded, multi-chamber frame and sash
- Heavy-duty weatherstripping
- Available frame styles: mounting fin, flange, finless
- 2 7⁄8" frame depth
- Available with brickmould accessory and integral J-channel
- Wood extension jambs available for 4 9⁄16" and 6 9⁄16" wall depths

## Min and max sizing

WIDTH		HEIGHT	
MIN	MAX	MIN	MAX
13"	48"	24"	96"
48"	52"	24"	84"
CONTINUOUS HEAD & SILL (CHS) MAX			
Twin (Each Window)	47 3⁄4"	84"	
Twin (Overall Unit)	95 5⁄8"	84"	
Triple (Each Window)	36"	84"	
Triple (Overall Unit)	108 3⁄4"	84"	

Available in 1/4" increments. DP upgrade required for any unit greater than 84" tall.  
CHS available on XX, XO, OX, XXX, and XOX configurations.

## Energy efficient glass

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Low-E glass	0.33	0.28	27
Low-E glass with grids	0.33	0.26	27
Argon and Low-E glass	0.30	0.28	27
Argon and Low-E glass with grids	0.30	0.26	27
HP Low-E glass	0.33	0.21	27
HP Low-E glass with grids	0.33	0.19	27
Argon and HP Low-E glass	0.30	0.21	27
Argon and HP Low-E glass with grids	0.30	0.19	27
Argon and LoE <sup>3</sup> -340 glass	0.30	0.15	27
Argon and LoE <sup>3</sup> -340 glass with grids	0.30	0.13	27

Note: all values based on standard 3/4" dual-pane insulated glass unit unless noted otherwise



**V2000 SERIES**  
**SINGLE-HUNG WINDOW**

See additional product and warranty information online.



Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

[miwindows.com/windows/V2000/single-hung](https://miwindows.com/windows/V2000/single-hung)

## Create a customized look

Enhance your home's spaces with a variety of finish options and grid configurations.

### FINISH OPTIONS

#### EXTERIOR

White EXTRUSION
Almond PAINT / EXTRUSION
Clay PAINT / EXTRUSION †
Cocoa PAINT ◊
Cream PAINT ◊
Forest Green PAINT ◊
Bronze LAMINATE ‡ / PAINT ◊
Black Matte LAMINATE ‡ / PAINT ◊

#### INTERIOR

White EXTRUSION
Almond EXTRUSION
Clay EXTRUSION †

### GRID TYPES



† Clay interior available on products manufactured in Texas only; may only be combined with clay extruded exterior  
‡ Exterior laminate available with white interior only; has a satin finish (matte applies to black paint only)  
◊ Exterior paint not available with brickmould