



4340
SINGLE-HUNG

4340 Vinyl Single-Hung Window

The 4340 vinyl single-hung window is a **DP50** version of the 4300 single-hung window that offers crafted features for exceptional durability and energy efficiency for new homes that require enhanced DP ratings. With standard features that include a pre-punched mounting fin and constant-force balance system, the 4340 single-hung window is made for both builders and homeowners in areas that require high-performance windows.

PERFORMANCE FEATURES

- Welded, multi-chambered frame and sash for superior strength and energy-efficiency
- Integral J-Channel and mounting fin with pre-punched holes for easy and efficient installation
- True-sloping sill optimizes water drainage and eliminates unsightly weep holes
- Metal-reinforced meeting rail, lock rail, and bottom sash rail delivers strength and durability
- Additional metal reinforcement in sash stiles

Welded multi-chamber mainframe design

3 1/4" frame depth

True-sloping sill



Dual-pane insulated glass

HIGH
PERFORMANCE

FLAT CASING

WARM-EDGE
SPACER SYSTEM

BRICKMOULD



DUAL-PANE



PAINTED
EXTERIOR

Standard

Optional

Designed smarter, from the inside out

ENGINEERED TO PERFORM

- Multi-chamber mainframe design
- 3 1/4" frame depth
- 3/4" insulating glass
- Wood extension jambs available for 4 9/16" and 6 9/16" wall depths
- Continuous head and sill mulling for twins and triples
- Factory-applied drywall returns available
- 2 frame styles available
 - fin, finless

CONVENIENCE & STYLE

The 4340 features the following design details on every window:

- Surface mounted tilt latches
- Full-length lift rail
- Easy sash and fixed glass removal
- Optional exterior brickmould and 3 1/2" flat casing

SAFETY & SECURITY FEATURES

- Optional tempered glass is four times stronger than non-tempered glass and safer if broken
- Optional obscure glass allows light in while protecting privacy
- Optional Window Operating Control Device (WOCD) restricts sash opening and reduces the risk of accidental falls

MIN & MAX SIZING

WIDTH		HEIGHT	
Min	Max	Min	Max
16 1/4"	44"	23"	83"

Available in 1/8" increments.

CREATE A CUSTOMIZED LOOK


GRID TYPES & SIZES

- 5/8" flat grids-between-the-glass
- 7/8" flat grids-between-the-glass
- 1 1/16" sculptured grids-between-the-glass
- 1 5/16" sculptured grids-between-the-glass
- 1 1/8" simulated divided light

GRID PATTERNS



Colonial



9-Lite Perimeter



6-Lite Perimeter



Diamond

INTERIOR/EXTERIOR EXTRUSIONS



White Extrusion



Almond Extrusion



Clay Extrusion

EXTERIOR PAINT*



Bronze



Black Matte

* Exterior paint available with 11/16" sculptured grids only; not available with clay interior

ENERGY-EFFICIENT GLASS PACKAGES

Our **dual-pane** insulated glass package options help save on heating and cooling costs while enhancing home comfort

- In cool weather**, insulated glass provides outstanding thermal performance to keep interior glass surfaces closer to room temperature, eliminating cold spots near windows
- In warm weather**, it helps reduce solar heat gain and minimize glare to improve interior comfort
- Able to meet **ENERGY STAR**® requirements in North-Central, South-Central, and Southern climate zones

GLAZING TYPE	U-VALUE	SHGC
Low-E glass	0.33	0.31
Low-E glass with grids	0.33	0.28
Argon and Low-E glass	0.30	0.31
Argon and Low-E glass with grids	0.30	0.28
HP Low-E glass	0.33	0.23
HP Low-E glass with grids	0.33	0.20
Argon and HP Low-E glass	0.30	0.22
Argon and HP Low-E glass with grids	0.30	0.20

Note: all values based on standard 3/4" dual-pane IGU



OUR MISSION

Getting It Right Every Time

We build each of our products the same way we built our company: with integrity and precision. Every MI window and door is handcrafted in the United States using state-of-the-art manufacturing techniques, and is backed by vigorous in-house testing procedures. We are 100% committed to offering the styles, value, and performance you're after.

Discover everything we have to offer at miwindows.com, or by calling 1-717-365-3300.

