



## V2000 Single-hung window

### MODEL 4340

Popular with builders, contractors, and homeowners, the 4340 single-hung window is specifically designed to meet high design pressure (DP) requirements. Combining a traditional brickmould exterior and timeless color options with optimally placed metal reinforcements and a constant-force balance system, these single-hung windows provide beauty and long-lasting strength and performance for new and existing homes.



## What you can expect

### ENERGY-EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

### CONVENIENCE AND STYLE

- Brickmould exterior profile creates timeless appeal
- Surface-mounted tilt latches and forced-entry-resistant locks provide a stronger, safer seal
- Full-length lift rail and constant-force balance system for easy opening and closing
- Tilt-in bottom sash for easy cleaning
- True-sloping sill optimizes water drainage and eliminates unsightly weep holes
- Easy sash and fixed glass removal for efficient drywall pass through during construction
- Optional window operating control device for enhanced safety



## Engineered to perform

- Welded, multi-chamber frame and sash
- Metal-reinforced meeting rail, lock rail, and bottom sash
- Available frame styles: mounting fin, finless
- 3 ¼" frame depth
- Integral J-channel
- Available with factory-applied drywall returns
- Wood extension jambs available for 4 ⅞" and 6 ⅞" wall depths

## Min and max sizing

WIDTH		HEIGHT	
MIN	MAX	MIN	MAX
16 ¼"	44"	23"	83"

Available in 1/8" increments.

## Energy efficient glass

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Low-E glass	0.33	0.28	28
Low-E glass with grids	0.33	0.25	28
Argon and Low-E glass	0.29	0.28	28
Argon and Low-E glass with grids	0.29	0.25	28
HP Low-E glass	0.33	0.23	28
HP Low-E glass with grids	0.33	0.20	28
Argon and HP Low-E glass	0.30	0.22	28
Argon and HP Low-E glass with grids	0.30	0.20	28

Note: all values based on standard 3/4" dual-pane insulated glass unit unless noted otherwise

## Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

### FINISH OPTIONS

#### EXTERIOR

White EXTRUSION
Almond EXTRUSION / PAINT ◊
Clay EXTRUSION †
Bronze PAINT ◊
Black Matte PAINT ◊

#### INTERIOR

White EXTRUSION
Almond EXTRUSION
Clay EXTRUSION †

### COMMON GRID TYPES

 Flat Grids-Between- the-Glass	 Sculptured Grids-Between- the-Glass	 Simulated Divided Lite
--	--	--

◊ Exterior paint not available with clay interior



**V2000 SINGLE-HUNG**  
See additional product and  
warranty information online.



Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

[miwindows.com/V2000](https://miwindows.com/V2000)