



What you can expect

ENERGY PERFORMANCE

Featuring the latest in energy performance, the V4500 can make the interior of your home more comfortable while helping you save on your energy bills.

- A warm-edge spacer system comes standard in the V4500 double-slider
- Options like HP Low-E glass coatings and argon gas between the panes can help improve energy performance

CONVENIENCE AND STYLE

- Exceptional detail gives the V4500 the appearance of a traditional wood window
- · Polyurethane window frame provides added comfort
- Obscure-glass options are available for privacy and aesthetics
- · Lift-out sashes make for easy maintenance
- Dual brass rollers featuring a stainless steel axle enable a worry-free performance
- · Narrow profiles enhance viewing space

Engineered to perform

- · Welded, multi-chamber frame and sash
- · Available frame styles: nail fin, finless
- Optional OptiView[™] Clarity mesh screen allows fresh air in while providing particle protection
- Product has passed rigorous testing for water penetration, air leakage, structural integrity, and forced entry

Min and max sizing

WIDTH		HE	HEIGHT			
MIN	мах	MIN	MAX			
22"	93"	13 1/4"	73"			
End Vent 3-Lite Slider 1/3-1/3-1/3 or 1/4-1/2-1/4						
45 1/4"	120"	13 1/4"	73"			
Center Vent 3-Lite Slider 1/3-1/3-1/3						
45 3/8"	120"	13 1/4"	73"			
End Vent 3-Lite Slider 1/3-1/3-1/3						
29 5/8"	120"	13 3/4"	67 ½"			
End Vent 3-Lite Slider 1/4-1/2-1/4						
39 1/4"	120"	13 3/4"	67 ½"			

Energy efficient glass

Able to meet ENERGY STAR® requirements in all four climate zones. Optional technologically-advanced SolarClean™ self-cleaning glass helps keep your glass naturally clean using ultraviolet sun rays to break down dirt and debris.

GLASS PACKAGE	SPACER	U-FACTOR	SHGC	ENERGY STAR ZONE
Ultra Max	4SG	0.28	0.33	
Ultra Max with Thermal-U Plus	4SG	0.24	0.32	NC
Extreme Ultra Max Triple-Pane	4SG	0.23	0.27	NC
Extreme Ultra Max Triple-Pane with Thermal-U Plus*	4SG	0.20	0.26	N, NC, SC, S
Omega Max	4SG	0.28	0.25	
Omega Max with Thermal-U Plus	4SG	0.24	0.25	NC
Passive Max	Black Endur	0.29	0.54	
Passive Max with Thermal-U Plus	Black Endur	0.25	0.52	N
Extreme Passive Max Triple-Pane with Thermal-U Plus	Black Endur	0.23	0.46	N

Exceeds AAMA Standard Air Leakage Rate of </= 0.03.

^{*}Qualifies for ENERGY STAR® Most Efficient tax credit.











Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

FINISH OPTIONS



GRID TYPES







Simulated Divided Lite



Simulated Meeting Rail



Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/windows/V4500/horizontal-slider