



## What you can expect

### FUNCTIONALITY

From its square appearance – achieved via an adjustable hinge system – to its energy performance, the V4550 is a utilitarian casement window that provides allencompassing efficiency.

- Low-profile, single-lever locking handle provides added security
- The V4550 boasts one of the industry's lowest air-infiltration rates

### CONVENIENCE AND STYLE

- · Available in several exterior frame colors
- Stepped internal and contoured external design maximizes the window's beauty
- Obscure-glass options are available for privacy and aesthetics
- Narrow profiles allow for more glass space, resulting in a viewing area that's 27% larger
- Dual weather-stripping system helps protect against drafts
- Optional 1 ¾" overall triple-glazed insulated high performance glass package enhances energy efficiency

# **Engineered to perform**

- · Welded, multi-chamber frame and sash
- · Available frame styles: nail fin, finless
- Optional OptiView™ Clarity mesh screen allows fresh air in while providing particle protection
- Product has passed rigorous testing for water penetration, air leakage, structural integrity, and forced entry

# Min and max sizing

| WIDTH          |     | HEIGHT  |     |  |
|----------------|-----|---------|-----|--|
| MIN            | мах | MIN     | MAX |  |
| 13 5/e"        | 36" | 20 5/8" | 80" |  |
| <b>36</b> ½16" | 40" | 20 5/8" | 60" |  |
| 40 1/16"       | 44" | 20 5/8" | 45" |  |

# **Energy efficient glass**

Able to meet ENERGY STAR® requirements in all four climate zones. Optional technologically-advanced SolarClean™ self-cleaning glass helps keep your glass naturally clean using ultraviolet sun rays to break down dirt and debris.

| GLASS PACKAGE  | SPACER      | U-FACTOR | SHGC | ENERGY<br>STAR<br>ZONE |
|--|-------------|----------|------|------------------------|
| Ultra Max  | 4SG         | 0.26     | 0.26 |                        |
| Ultra Max with Thermal U Plus                          | 4SG         | 0.23     | 0.26 | NC                     |
| Extreme Ultra Max Triple-Pane                          | 4SG         | 0.22     | 0.21 | N, NC, SC, S           |
| Extreme Ultra Max Triple-Pane with<br>Thermal U Plus*  | 4SG         | 0.20     | 0.20 | N, NC, SC, S           |
| Omega Max  | 4SG         | 0.26     | 0.19 | SC, S                  |
| Omega Max with Thermal U Plus                          | 4SG         | 0.22     | 0.19 | NC, SC, S              |
| Passive Max  | Black Endur | 0.27     | 0.46 |                        |
| Passive Max with Thermal U Plus                        | Black Endur | 0.23     | 0.44 | N                      |
| Extreme Passive Max Triple-Pane with<br>Thermal U Plus | Black Endur | 0.23     | 0.39 | N, NC                  |

Exceeds AAMA Standard Air Leakage Rate of </= 0.03.

## Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

#### FINISH OPTIONS



### GRID TYPES







Simulated Divided Lite



Simulated Meeting Rail











Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/windows/V4550/casement

<sup>\*</sup>Qualifies for ENERGY STAR® Most Efficient tax credit.