



## What you can expect

#### **ENERGY EFFICIENCY**

Our warm-edge spacer system, combined with options for Low-E glass coatings and argon gas between the panes, provides a superior energy performance.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare

#### CONVENIENCE AND STYLE

- Several windows and sliding glass doors from the V4550 series complement the single-hung
- · A variety of color options make it simple to find your style
- The bottom sash tilts in for easy cleaning and maintenance
- Dual pulley block-and-tackle balance system makes operation simple
- Optional FiberCore<sup>™</sup> fiberglass-reinforced meeting rail helps provide added strength and efficiency

By MITER Brands™ SUNRISE® SERIES / V4550

## **Engineered to perform**

- · Welded, multi-chamber frame and sash
- · Available frame styles: nail fin, finless
- Optional OptiView™ Clarity mesh screen allows fresh air in while providing particle protection
- Product has passed rigorous testing for water penetration, air leakage, structural integrity, and forced entry

## Min and max sizing

WIDTH		HEIGHT		
MIN	MAX	MIN	MAX	
13 <sup>5</sup> /8"	49"	22 1/2"	100"	
13 <sup>5</sup> /8"	52 3/4"	22 1/2"	83"	

For units over 60", UltraCore™ polyurethane and FiberCore™ fiberglass are required.

# **Energy efficient glass**

Able to meet ENERGY STAR® requirements in all four climate zones. Optional technologically-advanced SolarClean™ self-cleaning glass helps keep your glass naturally clean using ultraviolet sun rays to break down dirt and debris.

GLASS PACKAGE	SPACER	U-FACTOR	SHGC	ENERGY STAR ZONE
Ultra Max	4SG	0.28	0.29	
Ultra Max with Thermal U Plus	4SG	0.24	0.28	NC
Extreme Ultra Max Triple-Pane	4SG	0.23	0.23	NC, SC, S
Extreme Ultra Max Triple-Pane with Thermal U Plus	4SG	0.21	0.22	N, NC, SC, S
Omega Max	4SG	0.28	0.21	SC, S
Omega Max with Thermal U Plus	4SG	0.23	0.21	NC, SC, S

All values are for %" insulated glass without grids. Exceeds AAMA Standard Air Leakage Rate of </= 0.03.

### Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

#### FINISH OPTIONS



#### GRID TYPES















Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/windows/V4550/single-hung