



What you can expect

SUPERIOR STRENGTH

Whether you're looking for durability or home security, the V5500 has the added strength guaranteed to give you peace of mind.

- The V5500's FiberCore™ fiberglass reinforcement delivers front line strength
- Two low-profile locking handles supply next-level security

CONVENIENCE AND STYLE

- Standard Low-E glass coatings enhance energy performance
- Folding operator handle with easy-to-use crank mechanics creates a clean, modern aesthetic and delivers smooth, effortless operation
- · Narrow profiles enhance viewing space
- Optional 1 3/8" overall triple-glazed insulated high performance glass package enhances energy efficiency
- · Dual weather-stripping system protects against drafts
- · One of the industry's lowest air infiltration rates

Engineered to perform

- · Available frame styles: nail fin, finless
- · FiberCore $\!\!\!^{\mathbb{M}}$ fiberglass reinforcements enhance structural strength
- Options for Low-E glass coatings and argon gas help achieve ENERGY STAR® rating
- Product has passed rigorous testing for water penetration, air leakage, structural integrity, and forced entry
- Optional deeper Performance Sash allows the combination of ENERGY STAR® qualifying glass with blinds-between-the-glass and/or grids (overall 1 3/8" triple pane IGU)
- · Egress hardware is available to comply safety codes

Min and max sizing

WIDTH		HEIGHT		
MIN	MAX	MIN	мах	
21 5/8"	60"	13 ⁵ /8"	44"	

Energy efficient glass

Able to meet ENERGY STAR® requirements in all four climate zones. Optional technologically-advanced SolarClean™ self-cleaning glass helps keep your glass naturally clean using ultraviolet sun rays to break down dirt and debris.

GLASS PACKAGE	SPACER	U-FACTOR	SHGC	ENERGY STAR ZONE
Ultra Max	4SG	0.27	0.26	
Ultra Max with Thermal-U Plus	4SG	0.23	0.26	NC
Extreme Ultra Max Triple-Pane	4SG	0.22	0.21	N, NC, SC, S
Extreme Ultra Max Triple-Pane with Thermal U Plus*	4SG	0.20	0.20	N, NC, SC, S
Omega Max	4SG	0.26	0.19	SC, S
Omega Max with Thermal-U Plus	4SG	0.23	0.19	NC, SC, S
Passive Max	Black Endur	0.27	0.46	
Passive Max with Thermal-U Plus	Black Endur	0.24	0.44	N
Extreme Passive Max Triple-Pane with Thermal-U Plus	Black Endur	0.23	0.39	N, NC

All values are for №" insulated glass without grids. Exceeds AAMA Standard Air Leakage Rate of </= 0.03.

Create a customized look


Enhance your home's spaces with a variety finish options and grid configurations.

FINISH OPTIONS



GRID TYPES







Simulated Divided Lite



Simulated Meeting Rail











Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

miwindows.com/windows/V5500/awning

^{*}Qualifies for ENERGY STAR® Most Efficient tax credit.