



## V2000 Series

### Single-hung window

MODELS 1255 & 3500

Boasting a stylish look, these single-hung windows are favorites among builders and contractors for new home construction and replacement projects. The removable meeting rail, sash, and top-glass allow for easy drywall pass-through while multiple color options, stylish beveled profile, full-length lift rail, and metal reinforcements at the meeting rail provide homeowners with aesthetic options and desirable performance.



## What you can expect

### ENERGY-EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

### CONVENIENCE AND STYLE

- Beveled exterior profile creates a clean, timeless aesthetic
- Surface-mounted, forced-entry-resistant locks provide a stronger, safer seal
- Full-length lift rail for easy opening and closing
- Tilt-in bottom sash for easy cleaning
- Optional window operating control device for enhanced safety



## Engineered to perform

- Welded, multi-chamber frame and sash
- Available frame styles: fin, finless
- Heavy-duty weatherstripping
- 2 7/8" frame depth
- Available with brickmould accessory and integral J-channel\*
- Wood extension jambs available for 4 1/16" and 6 1/16" wall depths

## Min and max sizing

WIDTH		HEIGHT	
MIN	MAX	MIN	MAX
13"	48"	24"	96"
CONTINUOUS HEAD & SILL (CHS) MAX			
Twin (Each Window)	47 1/2"	83 1/2"	
Twin (Overall Unit)	95 1/8"	83 1/2"	
Triple (Each Window)	35 3/4"	83 1/2"	
Triple (Overall Unit)	107 1/2"	83 1/2"	

Available in 1/4" increments. DP upgrade required for any unit greater than 84" tall. CHS available on XX, XO, OX, XXX, and XOX configurations.

## Energy efficient glass

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Low-E glass	0.33	0.28	28
Low-E glass with grids	0.33	0.26	28
Argon and Low-E glass	0.29	0.28	28
Argon and Low-E glass with grids	0.29	0.26	28
HP Low-E glass	0.33	0.21	28
HP Low-E glass with grids	0.33	0.19	28
Argon and HP Low-E glass	0.29	0.21	28
Argon and HP Low-E glass with grids	0.29	0.19	28
Argon and Low-E Triple Pane glass	0.22	0.24	n/a
Argon, Low-E Triple Pane glass, and grids	0.22	0.21	n/a

Note: all values based on standard 3/4" dual-pane insulated glass unit unless noted otherwise



## Create a customized look

Enhance your home's spaces with a variety of finish options and grid configurations.

### FINISH OPTIONS

#### EXTERIOR



#### INTERIOR



### GRID TYPES



Grids-Between-the-Glass

Flat Sculptured

Simulated Divided Lite

\*J-Channel available on 3500 model only.

† Clay interior available on products manufactured in Texas only; may only be combined with clay extruded exterior.

‡ Exterior laminate available with white interior only; has a satin finish (matte applies to black paint only).

◊ Exterior paint not available with brickmould.

§ Black laminate interior available on black laminate exterior only.



Build boldly by choosing a range of MI window and door styles with expansive views, contemporary framing and hardware.

[miwindows.com/windows/V2000/single-hung](http://miwindows.com/windows/V2000/single-hung)